

## CLAIMS

1 1. A video amplifier comprising:

2 a first filter stage having an input terminal adapted to receive an RF signal and an output  
3 terminal;

4 an attenuator having an input terminal coupled to the output terminal of said first filter  
5 stage and an output terminal, said attenuator comprising a temperature sensitive device; and

6 a second filter stage having an input terminal coupled to the output terminal of the  
7 attenuator and an output terminal at which an output signal of said video amplifier is provided.

0 1 2. The video amplifier of claim 1 wherein said temperature sensitive device is a thermistor.

1 3. The video amplifier of claim 1 wherein each of said first filter stage and said second filter  
0 2 stage comprises a Sallen-Key filter.

1 4. The video amplifier of claim 1 wherein each of said first filter stage and said second filter  
0 2 stage has a low-pass characteristic.

1 5. The video amplifier of claim 1 wherein each of said first filter stage and said second filter  
Y 2 stage has a bandpass characteristic.

1 6. A radar receiver comprising:  
2 an RF amplifier having an input terminal adapted to receive an RF signal and an output  
3 terminal at which an amplified RF signal is provided;  
4 a down-converter having an input terminal coupled to said output terminal of said RF  
5 amplifier and an output terminal at which a lower frequency signal is provided; and  
6 a video amplifier having an input terminal coupled to said output terminal of said down-  
7 converter and an output terminal at which a filtered signal is provided, wherein said video  
8 amplifier comprises a temperature compensating attenuator.

0 1 7. The radar receiver of claim 6 wherein said RF amplifier is comprised of GaAs transistors.

0 1 8. The radar receiver of claim 6 wherein said attenuator comprises a thermistor.

0 1 9. The radar receiver of claim 8 wherein said attenuator further comprises at least one  
2 resistor coupled to said thermistor to form a voltage divider.

0 1 10. The radar receiver of claim 6 said video amplifier further comprises:  
2 a first filter stage having an input terminal coupled to said output terminal of said down-  
3 converter and an output terminal coupled to said temperature compensating attenuator; and  
4 a second filter stage having an input terminal coupled to said temperature compensating  
5 attenuator and an output terminal at which said filtered signal is provided.

1 11. The radar receiver of claim 9 wherein each of said first filter stage and said second filter  
 2 stage has a bandpass characteristic.

1 12. The radar receiver of claim 11 wherein said bandpass characteristic has a low frequency  
 2 cutoff selected to attenuate a leakage signal.

1 13. The radar receiver of claim 11 wherein said bandpass characteristic has a low frequency  
 2 cutoff selected to attenuate a received RF signal reflected by an object located more than a  
 3 predetermined distance from said RF receiver.

1 14. A radar system comprising:  
 2 a transmit antenna for transmitting a first RF signal;  
 3 a receive antenna for receiving a second RF signal; and  
 4 a receiver circuit coupled to said receive antenna for processing said second RF signal  
 5 and comprising a temperature compensated video amplifier.

1 15. The radar system of claim 14 wherein said temperature compensated video amplifier  
 2 comprises:

1 a first filter stage having an input terminal adapted to receive said second RF signal and  
 2 an output terminal;

3 an attenuator having an input terminal coupled to the output terminal of said first filter  
 4 stage and having an output terminal, said attenuator comprising a temperature sensitive device;  
 5 and

6 a second filter stage having an input terminal coupled to the output terminal of the  
7 attenuator and an output terminal at which an output signal of said video amplifier is provided.

1 16. The radar system of claim 15 wherein said receiver circuit further comprises an RF  
2 amplifier having a gain which varies by a first predetermined amount with temperature and  
3 wherein said attenuator provides a gain which varies by a second predetermined amount with  
4 temperature, wherein said first and second predetermined amounts are substantially equal.

1 17. The radar system of claim 14 wherein each of said first filter stage and said second filter  
2 stage has a bandpass characteristic.

1 18. The radar system of claim 17 wherein said second RF signal includes a portion of said  
2 first RF signal and wherein said bandpass characteristic has a low frequency cutoff selected to  
3 attenuate said portion of said first RF signal.

1 19. The radar system of claim 17 wherein said bandpass characteristic has a low frequency  
2 cutoff selected to attenuate a received RF signal reflected by an object located more than a  
3 predetermined distance from said radar system.

1 20. The radar system of claim 15 further comprising:  
2 an analog-to-digital converter responsive to said output signal of said video amplifier for  
3 providing a digital signal;

**U.S. DEPARTMENT OF JUSTICE**